

FOUR STROKE 4T SAE 10W/30 MA2

Synthetic blend motor oil for four-stroke motorbikes

Description

MOTOREX FOUR STROKE 4T is a synthetic blend, shear-stable motor oil that is also suitable for engines with wet multi-disc clutches.

Product attributes

- stable lubricating film
- temperature-stable
- shear-stable (stay-in-grade)

Field of application

MOTOREX FOUR-STROKE 4T is available in four further viscosity classes and is suitable for a wide range of motorbikes of all kinds without special requirements. Please always observe the manufacturer's specifications regarding viscosity and oil quality.

Specifications

API SG, API SH, API SJ, API SL, JASO MA2



JASO T 902 - 2016
PERFORMANCE IS GUARANTEED by
MOTOREX AG

Technical Data

Properties	Test according to	Unit	Values
Colour			yellowish-brown
Viscosity			SAE 10W/30
Density at 20 °C		g/cm ³	0.860
Viscosity at 40°C	DIN 51562-1	mm ² /s	64.5
Viscosity at 100°C	DIN 51562-1	mm ² /s	10.3
Viscosity index	DIN ISO 2909		147.0
Visco. according HTHS at 150°C	CEC-L-36 A-97	mPa.s	>= 2.9
Flash point	DIN EN ISO 2592	°C	>= 200
Pourpoint	ASTM D5950	°C	-39
NOACK	CEC L-40-A-93	%	9.60
TBN	DIN ISO 3771	mg KOH/g	6.90
CCS	ASTM D5293	mPa.s	5402
CCS Temperatur	ASTM D5293	°C	-25

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

MOTOREX USA Inc.

993 Federal Road
Brookfield, CT06804-1108, United States
Tel. +1 203-775-1291
motorex.com
02.02.2026 / 14

MOTOREX AG

Bern-Zürich-Strasse 31
4901 Langenthal, Schweiz
Tel. +41 62 919 75 75
motorex.com