

# LEGEND 4T

## SAE 20W/50

High-quality mineral-oil-based engine oil for 4-stroke motorcycles with separate engine and gearbox lubrication

### Description

High-quality mineral-oil-based engine oil for 4-stroke motorcycles with separate engine and gearbox lubrication. Thanks to the selection of base oils and additives specially adapted for this engine type, this engine oil provides optimum protection against wear and high temperature stability.

### Field of application

LEGEND 4T SAE 20W/50 has been specially developed for use in large two-cylinder engines. Ideal for air-cooled engines as well.

### Specifications

API SL; API SJ; API SH; API SG

### Advantages

- good wear protection
- high thermal stability
- optimal oil film, even at high temperatures
- ideal for high-capacity two-cylinder engines

### Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.880
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	169.0
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	19.0
Viscosity index		DIN ISO 2909	128
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥3.5
Pourpoint	°C	ASTM D5950	-24
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-15 / 8926
Sulphate residue content	%	DIN EN ISO 6245	1.4
NOACK	%	CEC L-40-A-93	6.8
TBN	mg KOH/g	DIN ISO 3771	8.2

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.