

# CROSS POWER 4T SAE 10W/60 MA2

Fully synthetic high-performance engine oil for 4-stroke Off-Road motorcycles

## Description

Fully synthetic high-performance 4-stroke engine oil, especially developed for Off-Road motorcycles. When this oil was developed, in close cooperation with racing teams and motorcycle manufacturers, attention was paid to the specific requirements of Off-Road use. JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

## Product features

- fully synthetic
- especially formulated for the toughest Off-Road use
- Racing quality
- extremely high thermal and shear stability
- Catalytic converter tested
- ideal for wet multi-disc clutches (JASO MA2 approval)



JASO T 903 '2016  
PERFORMANCE IS GUARANTEED BY  
MOTOREX AG

## Field of application

MOTOREX CROSS POWER 4T is available in three different viscosities for Off-Road use. Ideal for motorcycles with wet multi-disc clutches. Also meets the highest manufacturer's specifications.

## Notes

Warning: Harmful to water organisms; long-term effect.

## Specifications

API SM, API SN, API SP, JASO MA2, KTM LC4 2007+

## Technical Data

Properties	Test according to	Unit	Values
Colour			yellowish-brown
Viscosity			SAE 10W/60
Density at 20 °C		g/cm <sup>3</sup>	0.853
Viscosity at 40°C	DIN 51562-1	mm <sup>2</sup> /s	160.6
Viscosity at 100°C	DIN 51562-1	mm <sup>2</sup> /s	24.5
Viscosity index	DIN ISO 2909		185.0
Visco. according HTHS at 150°C	CEC-L-36 A-97	mPa.s	>= 3.5
Flash point	DIN EN ISO 2592	°C	>= 200
Pourpoint	ASTM D5950	°C	-42
NOACK	CEC L-40-A-93	%	5.00
Sulphate residue content	DIN EN ISO 6245	%	0.81
TBN	DIN ISO 3771	mg KOH/g	7.10
CCS	ASTM D5293	mPa.s	3490
CCS Temperatur	ASTM D5293	°C	-25

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.