

POWER SYNT 4T SAE 5W/40 MA2

Fully synthetic high-performance engine oil for 4-stroke hypersport motorcycles

Description

Fully synthetic high-performance 4-stroke engine oil, specially developed for demanding use in hypersport motorcycles with powerful engines. These lubrications provide engines, gearboxes and clutches with optimum protection over the entire range of applications. JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

Product features

- fully synthetic
- serious power delivery
- racing quality
- optimum wear protection
- extremely good thermal and shear stability
- catalytic converter tested
- ideal for wet multi-disc clutches (JASO MA2 approval)



JASO T 903 : 2016
PERFORMANCE IS GUARANTEED by
MOTOREX AG

Field of application

Available in three different viscosities, MOTOREX POWER SYNT 4T is specially designed for sporting use. Ideal for high-performance motorcycles with wet multi-disc clutches. Also meets the highest manufacturer's specifications.

Specifications

API SM, API SN, API SP, JASO MA2

Technical Data

Properties	Test according to	Unit	Values
Colour			yellowish-brown
Viscosity			SAE 5W/40
Density at 20 °C		g/cm ³	0.852
Viscosity at 40°C	DIN 51562-1	mm ² /s	88.5
Viscosity at 100°C	DIN 51562-1	mm ² /s	14.7
Viscosity index	DIN ISO 2909		174.0
Visco. according HTHS at 150°C	CEC-L-36 A-97	mPa.s	>= 3.5
Flash point	DIN EN ISO 2592	°C	>= 200
Pourpoint	ASTM D5950	°C	-45
NOACK	CEC L-40-A-93	%	5.70
Sulphate residue content	DIN EN ISO 6245	%	0.81
TBN	DIN ISO 3771	mg KOH/g	7.30
CCS	ASTM D5293	mPa.s	4300
CCS Temperatur	ASTM D5293	°C	-30

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.