

Printing date 02.04.2024

Version number 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CHAINLUBE RACING
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Only for proper handling.

Chain lubricant

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

- · Further information obtainable from: msds@motorex.com
- 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.

Skin Irrit. 2 H315 Causes skin irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

(Contd. on page 2)



Printing date 02.04.2024 Version number 1.0 Revision: 15.03.2024

Trade name: CHAINLUBE RACING

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
 P264 Wash thoroughly after handling.
 P273 Avoid release to the environment.

P280 Wear protective gloves.

P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	≥10-<20%
	Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<20%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	≥10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-7.5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C≥ 5%	0.25-1%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.1-<0.25

(Contd. on page 3)

MOTOREX*
Oil of Switzerland

Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 2)

≥30%

· Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Remove residues with soap and water.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

MOTOREX*
Oil of Switzerland

Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

106-9	97-8 L	outane, pure	
	Sho Long	rt-term value: 1810 mg/m³, 750 ppm g-term value: 1450 mg/m³, 600 ppm c (if more than 0.1% of buta-1.3-diene)	
110-5	54-3 ı	n-hexane	
WEL	Long	g-term value: 72 mg/m³, 20 ppm	
110-8	32-7	cyclohexane	
WEL		rt-term value: 1050 mg/m³, 300 ppm g-term value: 350 mg/m³, 100 ppm	
DNEL	Ls		
Hydro	ocari	bons, C7-C9, n-alkanes, isoalkanes, cyclics	
Oral		DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Derm	nal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
		DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
nhala	ative	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m3 (worker)
		DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)
Kohle	enwa	sserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5	% n-Hexan
Oral		DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Derm	nal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
		DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Inhala	ative	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m3 (worker)
		DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)
Hydro	ocar	bons, C9-C11, n-alkanes, isoalkanes, cycloalkanes,	<2% aromatics
Oral		DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)
Derm	nal	DNEL / Workers / Systemic effects / Long-term	300 mg/kg/24h (worker)
		DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)
Inhalative		DNEL / Workers / Systemic effects / Long-term	1,500 mg/m3 (worker)
		DNEL/general population/Systemic effects/Long-term	900 mg/m3 (consumer)
110-8	32-7	cyclohexane	
Oral		DNEL/general population/Systemic effects/Long-term	59.4 mg/kg/24h (consumer)
Derm	nal	DNEL / Workers / Systemic effects / Long-term	2,016 mg/kg/24h (worker)
		DNEL/general population/Systemic effects/Long-term	1,186 mg/kg/24h (consumer)
		DNEL / Workers / Systemic effects / Long-term	700 mg/m3 (worker)



Printing date 02.04.2024

Version number 1.0

Trade name: CHAINLUBE RACING

	(Contd. of page 4)
DNEL/Workers/Systemic effects/acute-short term	700 mg/m3 (worker)
DNEL/Workers/Local effects/acute-short term	700 mg/m3 (worker)
DNEL / Workers / Local Effects / Long-term	700 mg/m3 (worker)
DNEL/general population/Systemic effects/Long-term	206 mg/m3 (consumer)
DNEL/general pop/Systemic effects/acute-short term	412 mg/m3 (consumer)
DNEL/general pop/Local effects/acute-short term	412 mg/m3 (consumer)
DNEL/general population/Local effects/Long-term	206 mg/m3 (consumer)

PNECs

110-82-7 cyclohexane

,	
PNEC / Aquatic organisms / Freshwater	0.207 mg/l (aquatic organisms)
PNEC / Aquatic organisms / Marine water	0.207 mg/l (aquatic organisms)
PNEC/Aquatic organisms/Sewage treatment plant/STP	3.24 mg/l (aquatic organisms)
PNEC / Aquatic organisms / Sediment (freshwater)	3.627 mg/kg (aquatic organisms)
PNEC / Aquatic organisms / Sediment (marine water)	3.627 mg/kg (aquatic organisms)
PNEC / Terrestrial organism / Soil	2.99 mg/kg (terrestrial organisms)

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Not required.
- · Body protection: Protective work clothing

- GE

MOTOREX Oil of Switzerland

Printing date 02.04.2024 Version number 1.0 Revision: 15.03.2024

Trade name: CHAINLUBE RACING

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol

white
Solvent-like
Not determined.

Undetermined.

· Boiling point or initial boiling point and

boiling range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: <-20 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Consistency

• **Dynamic:** Not determined.

Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

Heat Capacity

· Vapour pressure: Not determined.

Density and/or relative density

• **Density at 20 °C:** 0.73 g/cm³ (ASTM D 4052)

Relative densityVapour densityNot determined.Not determined.

9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

· **VOC (EC)** 73.00 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes
⋅ Explosives Void
⋅ Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised

container: May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Void
Pyrophoric solids

(Contd. on page 7)



Printing date 02.04.2024 Version number 1.0 Revision: 15.03.2024

Trade name: CHAINLUBE RACING

		(Contd. of page 6
· Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		t for classification:	
106-97-8 butane, pure Inhalative LC50 / 15 min 1,442.738-1.443 mg/l (rat)			
		800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	LC50 / 4h	658 mg/l (rat)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.2-21.4 mg/l (rat)	
	LOAEC	21.6 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	
Hydrocar	bons, C7-C9, n	-alkanes, isoalkanes, cyclics	
Oral	LD50	8 ml/kg (rat)	
Dermal	LD50	4 ml/kg (rat)	
	LD50	2,800-3,100 mg/kg (rat)	
Inhalative	LC50 / 4h	23.3 mg/l (rat)	
	NOAEC	5.8-24.3 mg/l (rat)	
Kohlenwa	asserstoffe C6-	C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan	
Oral	LD50	8 ml/kg (rat)	
Dermal	LD50	4 ml/kg (rat)	
	LD50	2,800-3,100 mg/kg (rat)	
Inhalative	LC50 / 4h	25.2 mg/l (rat)	
	NOAEC	8.117-24.3 mg/l (rat)	



Printing date 02.04.2024

Version number 1.0

Trade name: CHAINLUBE RACING

			(Contd. of page
Hydrocar	bons, C9-C11,	n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	
Oral	LD50	5,000-15,000 mg/kg (rat)	
	NOAEL	1,000-5,000 mg/kg/24h (rat)	
Dermal	LD50	2,000 mg/kg (rat)	
		3,160-5,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)	
	LC50 / 8h	41-4,467 ppm (rat)	
	LC50 / 8h	5 mg/l (rat)	
	NOAEL	200 ppm (rat)	
	NOAEC	275-10,400 mg/m3 (rat)	
74-98-6 p	ropane		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)	
	LC50 / 15 min	800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.214-21.394 mg/l (rat)	
	LOAEC	21.64 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	
110-82-7	cyclohexane		
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	32.88 mg/l (rat)	
	LC50 / 4h	5,540 ppm (rat)	
	NOAEC	500-2,000 ppm (mouse)	
		500-7,000 ppm (rat)	

- Skin corrosion/irritation Causes skin irritation.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquation	· Aquatic toxicity:		
106-97-	106-97-8 butane, pure		
LC50	24.1-147.5 mg/l/96h (fish)		
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)		
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)		
Hydrod	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
EC50	0.23 mg/l/21d (aquatic invertebrates)		
EC50	0.64 mg/l/48h (aquatic invertebrates)		
LL50	3-10 mg/l/96h (fish)		
LL50	10-30 mg/l/72h (fish)		
LL50	10-30 mg/l/48h (fish)		
	(Contd. on page 0)		

(Contd. on page 9)

MOTOREX Oil of Switzerland
Revision: 15.03.2024

Printing date 02.04.2024

Version number 1.0

Trade name: CHAINLUBE RACING

			(Contd. of page 8)
	LL50	30-100 mg/l/24h (fish)	(
	LL0	3 mg/l/96h (fish)	
	EL50	13 mg/l/96h (algae / cyanobacteria)	
	EL50	4.6-10 mg/l/48h (aquatic invertebrates)	
		10-30 mg/l/48h (algae / cyanobacteria)	
	EL50	10-22 mg/l/24h (aquatic invertebrates)	
		10-30 mg/l/24h (algae / cyanobacteria)	
	EL50	10-30 mg/l/72h (algae / cyanobacteria)	
	EL0	4.6 mg/l/48h (aquatic invertebrates)	
	EL0	10 mg/l/24h (aquatic invertebrates)	
	NOEC	0.17 mg/l/21d (aquatic invertebrates)	
	NOELR	0.574 mg/l/28d (fish)	
	NOELR	1 mg/l/21d (aquatic invertebrates)	
	NOELR	6.3 mg/l/96h (algae / cyanobacteria)	
	LOEC	0.32 mg/kg/28d (aquatic invertebrates)	
	Kohlenv	wasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan	
	EC50	0.23 mg/l/21d (aquatic invertebrates)	
	EC50	0.64 mg/l/48h (aquatic invertebrates)	
	LL50	11.4 mg/l/96h (fish)	
	LL50	15.8 mg/l/72h (fish)	
	LL0	5.1 mg/l/96h (fish)	
	EL50	3 mg/l/48h (aquatic invertebrates)	
	EL50	12 mg/l/24h (aquatic invertebrates)	
	EL50	10-100 mg/l/72h (algae / cyanobacteria)	
	EL0	2 mg/l/48h (aquatic invertebrates)	
	EL0	10 mg/l/24h (aquatic invertebrates)	
	NOEC	0.17 mg/l/21d (aquatic invertebrates)	
	NOELR	2.045 mg/l/28d (fish)	
	NOELR	1 mg/l/21d (aquatic invertebrates)	
	LOEC	0.32 mg/kg/28d (aquatic invertebrates)	
	Hydroca	arbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	
	LL50	1,000 mg/l/96h (fish)	
	LL50	1,000 mg/l/72h (fish)	
	LL50	1,000 mg/l/48h (fish)	
	LL50	1,000 mg/l/24h (fish)	
	LL0	100 mg/l/96h (fish)	
	EL50	1,000 mg/l/48h (aquatic invertebrates)	
	EL50	1,000 mg/l/24h (aquatic invertebrates)	
	EL50	1,000 mg/l/72h (algae / cyanobacteria)	
	EL0	1,000 mg/l/48h (aquatic invertebrates)	
	NOELR	0.131 mg/l/28d (fish)	
	NOELR	0.23 mg/l/21d (aquatic invertebrates)	
	NOELR	3-100 mg/l/72h (algae / cyanobacteria)	
	74-98-6	propane	
	LC50	24.11-147.54 mg/l/96h (fish)	
	LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)	
_			(Contd. on page 10)

Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

	(Contd. of page 9)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)
110-82-	7 cyclohexane
LC50	4.53 mg/l/96h (fish)
EC50	0.9-2.4 mg/l/96h (aquatic invertebrates)
EC50	3.4-9.317 mg/l/72h (algae / cyanobacteria)
NOEC	0.9-0.94 mg/l/72h (algae / cyanobacteria)

. 12 2 Persistence and degradability No further relevant information available

· 12.2 Persistence and degradability No further relevant Information available.			
· 12.3 Bioaccumulative potential			
106-97-8 butane, p	ure		
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)		
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Biodegradability	98 % (28d) (Biodegradability) (OECD 301 F)		
Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan			
Biodegradability	81 % (28d) (Biodegradability) (OECD 301 F)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
Biodegradability	80 % (28d) (Bioaccumulation) (OECD 301 F)		
74-98-6 propane			
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)		
110-82-7 cyclohexane			
Partition coefficient	3.44 [] (log Kow) (Bioaccumulation)		
Biodegradability	77 % (28d) (Biodegradability) (OECD 301 F)		

- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

· Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 11)



Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 10)

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport informa	tion
14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN	1950 AEROSOLS, ENVIRONMENTAL HAZARDOUS
IMDG IATA	AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR/RID/ADN	
Class Label	2 5F Gases. 2.1
IMDG	
Class	2.1 Gases. 2.1
Label IATA	2.1
2	
Class Label	2.1 Gases.
14.4 Packing group	2.1
ADR/RID/ADN, IMDG, IATA	Not classified as hazardous for transport
14.5 Environmental hazards:	Product contains environmentally hazard substances: Hydrocarbons C6-C7, n-alkanes, alkanes, cyclenes, <5% n-hexane
Marine pollutant:	No Symbol (fish and tree)
Special marking (ADR/RID/ADN):	Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler	
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat.
Sionage Code	SW22 For AEROSOLS with a maximum capa of 1 litre: Category A. For AEROSOLS wit capacity above 1 litre: Category B. For WAS
Segregation Code	AEROSOLS: Category C, Clear of living quarter SG69 For AEROSOLS with a maximum capa of 1 litre:



Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

	(Contd. of page 1
	Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity 2
· Transport category · Tunnel restriction code	D D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMĂBLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

- GE

Printing date 02.04.2024 Version number 1.0 Revision: 15.03.2024

Trade name: CHAINLUBE RACING

(Contd. of page 12)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· purity requirement

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Abteilung Produktsicherheit

Abbreviations and acronyms:

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Annex: Exposure scenario 1

- · Short title of the exposure scenario Industrial use of sprays
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.

(Contd. on page 14)

MOTOREX*
Oil of Switzerland
Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0 Re

Trade name: CHAINLUBE RACING

(Contd. of page 13)

- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 2

- · Short title of the exposure scenario Professional use of sprays
- Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging

(Contd. on page 15)

MOTOREX Oil of Switzerland
Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 14)

- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of sprays
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- Process category PROC11 Non industrial spraying
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- Physical parameters
- Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 4

- · Short title of the exposure scenario Industrial use of lubricants and greases in open systems
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC7 Industrial spraying

(Contd. on page 16)

MOTOREX Oil of Switzerland
Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 15)

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 5

- · Short title of the exposure scenario Professional use of lubricants and greases in open systems
- Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

(Contd. on page 17)

MOTOREX Oil of Switzerland
Revision: 15.03.2024

Printing date 02.04.2024 Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 16)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 6

- · Short title of the exposure scenario Private use of lubricants and greases in open systems
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category PC24 Lubricants, greases, release products
- Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.

(Contd. on page 18)

MOTOREX*
Oil of Switzerland
Revision: 15.03.2024

Printing date 02.04.2024

Version number 1.0

Trade name: CHAINLUBE RACING

(Contd. of page 17)

- · Environmental protection measures
- Air No special measures required.
- Water No special measures required.
- Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB