MOTOREX Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

## SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: RACING PRO 4T SAE 15W/50
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Only for proper handling.

Engine oil

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

- · Further information obtainable from: msds@motorex.com
- 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 (UK only).

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms Void
- Signal word Void
- Hazard statements

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains maleic anhydride. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)



Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

		(Contd. of page 1)
· Dangerous components:		
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1, H304	≥2.5-≤7.5%
	Mineral oils (mixture) Asp. Tox. 1, H304	≥2.5-≤7.5%
CAS: 84605-29-8 EINECS: 283-392-8 Reg.nr.: 01-2119493626-26	Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc salts  Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315 Specific concentration limits: Skin Irrit. 2; H315: C≥ 6.25 % Eye Dam. 1; H318: C≥ 12.5 % Eye Irrit. 2; H319: 10 % ≤ C < 12.5 %	≥1-<2.5%
EC number: 947-519-7	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. Para-, calcium salts Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B; H317:C ≥ 10.01 %	≥0.1-≤1%
CAS: 121158-58-5 EC number: 310-154-3 Index number: 604-092-00-9 Reg.nr.: 01-2119513207-49	phenol, dodecyl-, branched Repr. 1B, H360F; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10)	≥0.0025-<0.025%
CAS: 108-31-6 EINECS: 203-571-6 Index number: 607-096-00-9	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317:C ≥ 0.001 %	≥0-<0.001%

#### · Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

- GE

MOTOREX Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 2)

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and phosphorus oxides can be formed.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.

- · Information about fire and explosion protection: Do not heat above flash point.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

- Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-31-6 maleic anhydride

WEL | Short-term value: 3 mg/m<sup>3</sup>

Long-term value: 1 mg/m3

Sen

· DNELs

64742-55-8 Distillates (petroleum), hydrotreated light paraffinic

Dermal | DNEL / Workers / Local Effects / Long-term | 1 mg/kg/8h (worker)

Inhalative DNEL 2.7-5.4 mg/m3/8h (worker)

(Contd. on page 4)

MOTOREX\*
Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

Oral	-8 Phoenhorodithioic acid mixed O.O.		
	salts	bis (1,3-diet	hylbutyl and iso-Pr)esters, zii
	DNEL/general population/Systemic effect	ts/Long-term	0.24 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long	g-term	12.1 mg/kg/24h (worker)
	DNEL/general population/Systemic effect	ts/Long-term	6.1 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long	g-term	8.31 mg/m3 (worker)
	DNEL/general population/Systemic effect	ts/Long-term	2.11 mg/m3 (consumer)
121158-58	8-5 phenol, dodecyl-, branched		
Oral	DNEL/general population/Systemic effect	ts/Long-term	0.075 mg/kg/24h (consumer)
	DNEL/general pop/Systemic effects/acute	e-short term	1.26 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long	g-term	0.25 mg/kg/24h (worker)
	DNEL/Workers/Systemic effects/acute-sl	hort term	166 mg/kg/24h (worker)
	DNEL/general population/Systemic effect	ts/Long-term	0.075 mg/kg/24h (consumer)
	DNEL/general pop/Systemic effects/acute	e-short term	50 mg/kg/24h (consumer)
Inhalative	DNEL/Workers/Systemic effects/acute-sl	hort term	44.18 mg/m3 (worker)
	DNEL/general population/Systemic effect	ts/Long-term	0.79 mg/m3 (consumer)
	DNEL/general pop/Systemic effects/acute	e-short term	13.26 mg/m3 (consumer)
PNECs			
	-8 Distillates (petroleum), hydrotreated	light paraffir	nic
	EC / Predators / Secondary poisoning	<u> </u>	g food (secondary poisoni
	,, ,	(predators))	
84605-29-	<ul><li>-8 Phosphorodithioic acid, mixed O,O- salts</li></ul>	bis (1,3-diet	hylbutyl and iso-Pr)esters, zii
Oral PNE	EC / Predators / Secondary poisoning	10.67 mg/k (predators))	kg food (secondary poisonii
PNE	EC / Aquatic organisms / Freshwater	• ,	aquatic organisms)
ı	EC / Aquatic organisms / Marine water	•	(aquatic organisms)
	EC/Aquatic org/intermittent ases(freshwater)	0.045 mg/l (a	aquatic organisms)
plan	PNEC/Aquatic organisms/Sewage treatment 100 mg/l (aquatic organism plant/STP		· ·
	EC / Aquatic organisms / Sediment shwater)	nent 0.02203 mg/kg (aquatic organisms) nent 0.002203 mg/kg (aquatic organisms)	
(mar	rine water)		
	EC / Terrestrial organism / Soil	0.00206 mg/	kg (terrestrial organisms)
	8-5 phenol, dodecyl-, branched		
	EC / Predators / Secondary poisoning	poisoning 4 mg/kg food (secondary poiso (predators))	
ı	EC / Aquatic organisms / Freshwater	-	g/l (aquatic organisms)
	EC / Aquatic organisms / Marine water		ng/l (aquatic organisms)
	EC/Aquatic org/intermittent ases(freshwater)	0.00037 mg/	l (aquatic organisms)
	EC/Aquatic organisms/Sewage treatment t/STP	100 mg/l (aq	uatic organisms)
	EC / Aquatic organisms / Sediment shwater)	0.226 mg/kg	(aquatic organisms)

MOTOREX Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 4)

PNEC / Aquatic organisms / Sediment 0.0266 mg/kg (aquatic organisms)

(marine water)

PNEC / Terrestrial organism / Soil 0.118 mg/kg (terrestrial organisms)

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eve/face protection Goggles recommended during refilling
- · Body protection: Protective work clothing

#### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:FluidBrown

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range Undetermined.
Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: >200 °C

Auto-ignition temperature:
 Decomposition temperature:
 pH
 255 °C (DIN 51794)
 Not determined.
 Not determined.

Viscosity:

• Kinematic viscosity 115.4 mm²/s @ 40 °C

. 17.7 mm²/s @ 100 °C · Consistency

• **Dynamic:** Not determined.

(Contd. on page 6)



Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 5)

· Solubility

· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value)

Not determined.

Heat Capacity

· Vapour pressure:

<0.1 hPa (20°C)

Density and/or relative density

· Density at 20 °C:

0.872 g/cm3 (ASTM D 4052)

Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form:

Fluid

· Important information on protection of health

and environment, and on safety.

Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

· VOC (EC)

0.00 %

Void

Change in condition

Not determined. · Evaporation rate

· Information with regard to physical hazard

classes · Explosives

Void

Flammable gases Void · Aerosols Void

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void

Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

· Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water Void · Oxidising liquids Void Void · Oxidising solids Void · Organic peroxides Void

· Corrosive to metals · Desensitised explosives Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.



Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 6)

### SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		evant for classification:
64742-55-	8 Distillate	es (petroleum), hydrotreated light paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
84605-29-		orodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc
	salts	
Oral	NOEL	40 mg/kg/24h (rat)
	NOAEL	160 mg/kg/24h (rat)
Dermal	LD50	2,002 mg/kg (rat)
Inhalative	LC50 / 4h	2.3 mg/l (rat)
121158-58	3-5 phenol,	, dodecyl-, branched
Oral	LD50	2,100-2,200 mg/kg (rat)
	NOEL	5-50 mg/kg/24h (rat)
	NOAEL	60-100 mg/kg/24h (rat)
Dermal	LD50	15,000 mg/kg (rabbit)
108-31-6 i	maleic anh	ydride
Oral	LD50	400 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)
Claire a sur	!/!!	tion Resed on available data, the classification criteria are not met

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties	
121158-58-5 phenol, dodecyl-, branched	List I

MOTOREX Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 7)

#### · 12.1 Toxicity

· 12.1 Tox · Aquatic	•
64742-5	5-8 Distillates (petroleum), hydrotreated light paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
	>100 mg/l/96h (Pimephales promelas) (OECD 203)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
NOEL	>100 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201)
84605-2	9-8 Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zin salts
LOEC	0.8 mg/l/21d (aquatic invertebrates)
LC50	46 mg/l/96h (fish)
EC50	10,000 mg/l/3h (microorganisms)
LL50	4.5 mg/l/96h (fish)
EL50	23 mg/l/48h (aquatic invertebrates)
EL50	21-24 mg/l/72h (algae / cyanobacteria)
NOEC	0.4-0.8 mg/l/21d (aquatic invertebrates)
NOELR	1.8 mg/l/96h (fish)
NOELR	10 mg/l/48h (aquatic invertebrates)
Reaction calcium	n products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. Para-, salts
LC50	>1,000 mg/l/96h (Pimephales promelas)
	>100 mg/l/96h (rainbow trout)
EC50	>1,000 mg/l/96h (algae)
121158-	58-5 phenol, dodecyl-, branched
EC50	1,000 mg/l/3h (microorganisms)
EC50	0.106 mg/l/24h (aquatic invertebrates)
EC10	0.53-0.765 mg/l/72h (algae / cyanobacteria)
EC50	0.15-0.765 mg/l/72h (algae / cyanobacteria)
EC50	0.0079-0.0086 mg/l/21d (aquatic invertebrates)
EC100	160 mg/l/48h (aquatic invertebrates)
EC0	0.056 mg/l/48h (aquatic invertebrates)
EC50	0.037-0.0927 mg/l/48h (aquatic invertebrates)
EL50	40 mg/l/96h (fish)
NOEC	0.0037 mg/l/21d (aquatic invertebrates)
NOEC	0.07-0.442 mg/l/72h (algae / cyanobacteria)
NOEC	0.011 mg/l/48h (aquatic invertebrates)
NOEC	1,000 mg/l/3h (microorganisms)
	25 mg/l/96h (fish)
LOEC	0.012 mg/kg/28d (aquatic invertebrates)
	sistence and degradability No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 9)

Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

	(Contd. of page 8)
· 12.3 Bioaccumulat	tive potential
64742-55-8 Distilla	tes (petroleum), hydrotreated light paraffinic
Partition coefficient	>3.5 [] (log Kow) (Bioaccumulation)
84605-29-8 Phospi salts	horodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc
Partition coefficient	0.56 [] (log Kow) (Bioaccumulation)
1	ol, dodecyl-, branched
Partition coefficient	6.1-7.14 [] (log Kow) (Bioaccumulation)
Biodegradability	<10 % (28d) (Biodegradability) (OECD 302 D)

- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR/RID/ADN, ADN, IMDG, IATA	Not classified as hazardous for transport
14.2 UN proper shipping name ADR/RID/ADN, ADN, IMDG, IATA	Not classified as hazardous for transport
14.3 Transport hazard class(es)	
ADR/RID/ADN, ADN, IMDG, IATA Class	Not classified as hazardous for transport
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Not classified as hazardous for transport
14.5 Environmental hazards: Marine pollutant:	No

MOTOREX\*
Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

	(Contd. of page 9
· 14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accord	ing to Not applicable.
· UN "Model Regulation":	Not classified as hazardous for transport

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National chemical directories Components listed or exempted from listing:
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

#### · purity requirement

#### Relevant phrases

H302	Harmful if swallowed	

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H360F May damage fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Department issuing SDS: Abteilung Produktsicherheit

#### · Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

(Contd. on page 11)

MOTOREX\*
Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 10)

\* Data compared to the previous version altered.

### Annex: Exposure scenario 1

· Short title of the exposure scenario

Industrial use of lubricants and greases in vehicles or machinery

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC16 Heat transfer fluids

PC17 Hydraulic fluids

PC24 Lubricants, greases, release products

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC7 Use of functional fluid at industrial site

- Description of the activities / processes covered in the Exposure Scenario
   See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB

MOTOREX\*
Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 11)

### Annex: Exposure scenario 2

#### · Short title of the exposure scenario

Professional use of lubricants and greases in vehicles or machines

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### · Product category

PC16 Heat transfer fluids

PC17 Hydraulic fluids

PC24 Lubricants, greases, release products

#### Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC20 Use of functional fluids in small devices

#### · Environmental release category

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

#### · Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

### Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of lubricants and greases in vehicles or machines
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers

(Contd. on page 13)

MOTOREX\*
Oil of Switzerland
Revision: 19.09.2023

Printing date 19.09.2023

Version number 3.0 (replaces version 2.0)

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 12)

- · Product category PC24 Lubricants, greases, release products
- Environmental release category

ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- Worker protection
- Organisational protective measures No special measures required.
- Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB